## NSN 3020-00-756-1336

Spur Gear - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/3020-00-756-1336

view Online at https://aerobasegroup.com/hsh/3020-00-70	.0-
Body Style:	
Webbed, solid	
Attachment Method:	
Mounting hole	
Pitch Diameter:	
Between 0.6865 inches and 0.6875 inches	
Teeth Quantity:	
44	
Bore Style:	
Plain both ends	
Mounting Hole Thread Series Designator:	
Unc transversely through hub, first end	
Mounting Hole Thready Qty Per Inch (tpi):	
32 transversely through hub, first end	
Mounting Hole Thread Size:	
0.138 inches transversely through hub, first end	
Mounting Hole Type And Quantity:	
2 threaded transversely through hub, first end	
Outside Diameter:	
0.718 inches	
Nominallength:	
0.375 inches	
Tooth Form:	
Standard	
Pressure Angle:	
20.0000 degrees	
Distance Between Body Face And Protruding Hub End	1:
0.120 inches first end	
Face Width:	
0.125 inches	
Bore Diameter:	
0.250 inches both ends	
Hub Style Designator:	
Plain first end	
Hub Diameter:	
0.500 inches first end	
Precision Classification:	
Quality number 10 or quality number 11	
Material:	
Aluminum	
Material Specification:	

Qq-a-267, type 24st federal specification single material response

## NSN 3020-00-756-1336

Spur Gear - Page 2 of 2



Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.