## NSN 3020-00-761-2203



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-761-2203 **Body Style:** Webbed, with lightening holes **Spline Quantity:** 21 both ends Pitch Diameter: 4.1110 inches **Teeth Quantity:** 74 **Bore Style:** Straight spline both ends Hardness Rating: 80.0 rockwell a and 82.5 rockwell a teeth **Outside Diameter:** 4.222 inches Nominallength: 1.000 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches both ends **Face Width:** 0.750 inches **Bore Diameter:** 1.250 inches both ends **Counterbore Depth:** 0.200 inches both ends **Counterbore Diameter:** 1.438 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.750 inches first end Material: Steel comp 4620 **Material Specification:** Mil-s-7493, comp 4620 military specification single material response **Style Designator:** Protruding hubs Shelf Life:

N/a

## NSN 3020-00-761-2203

Spur Gear - Page 2 of 2



	In	i+	∩f	RA.	~~	cii	re:
u	,,,	Iι	vı	IVI	ca.	่อน	ıe.

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7493 spec.