NSN 3020-00-761-8448



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-761-8448 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.4583 inches **Teeth Quantity:** 105 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.486 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.188 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.187 inches first end **Precision Classification:** Quality number 10 or quality number 11

End Diameter: 0.500 inches first end

First Step Length:

0.063 inches first end

NSN 3020-00-761-8448

Spur Gear - Page 2 of 2



First Step Diameter:
0.875 inches first end
Material:
Steel comp 303
Material Specification:
Mil-s-7720 military specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-s-7720 spec.