## NSN 3020-00-761-9068

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-761-9068

Body Style:
Plain, solid
Pitch Diameter:
Between 0.8740 inches and 0.8750 inches
Teeth Quantity:
42
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.916 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.500 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 lubricant impregnated bearing
Shelf Life:

N/a

## **NSN 3020-00-761-9068** Spur Gear - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A27300