NSN 3020-00-763-1306

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-763-1306

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| Between 1.5462 inches and 1.5469 inches |
| Teeth Quantity: |
| 99 |
| Hardness Rating: |
| 28.0 rockwell c and 32.0 rockwell c hub |
| Outside Diameter: |
| 1.577 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.135 inches second end |
| Face Width: |
| 0.096 inches |
| Hub Style Designator: |
| 1 step both ends |
| End Length: |
| 0.265 inches first end |
| Precision Classification: |
| Quality number 12 |
| End Diameter: |
| 0.250 inches second end |
| First Step Length: |
| 0.010 inches second end |
| First Step Diameter: |
| 0.282 inches second end |
| Material: |
| Steel comp 416 hub |
| Material Specification: |
| Qq-s-764, cond t-canceled federal specification single material response hub |
| Surface Treatment: |
| Oxide film body |
| Surface Treatment Specification: |
| Mil-c-5541 federal specification single treatment response body |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |

NSN 3020-00-763-1306

Spur Gear - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.