## NSN 3020-00-763-6000

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-763-6000

## **Body Style:**

Webbed, with lightening holes

#### **Attachment Method:**

Mounting hole

#### **Pitch Diameter:**

1.5310 inches

## **Teeth Quantity:**

98

Bore Style:

Plain both ends

#### Mounting Hole Type And Quantity:

2 plain transversely through hub, first end

#### **Outside Diameter:**

1.561 inches

**Tooth Form:** 

Standard

## **Pressure Angle:**

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.293 inches first end

## Face Width:

0.188 inches

## Bore Diameter:

0.187 inches both ends

#### Hub Style Designator:

Plain both ends

#### Hub Diameter:

0.375 inches second end

### **Precision Classification:**

Quality number 12

### Mounting Hole Diameter:

0.052 inches transversely through hub, first end

#### Material:

Aluminum alloy 2024

### **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

## Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

#### Style Designator:

Protruding hubs

# NSN 3020-00-763-6000

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-c-5541 spec.

