NSN 3020-00-763-8680



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-763-8680 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.5000 inches **Teeth Quantity:** 96 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.531 inches Nominallength: 0.312 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end Material: Steel comp 303 **Material Specification:** Mil-s-7720, comp 303s military specification single material response **Surface Treatment: Passivate**

Style Designator:

Protruding hub

NSN 3020-00-763-8680

Spur Gear - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.