## NSN 3020-00-765-4911

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-765-4911 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.4490 inches and 0.4500 inches **Teeth Quantity:** 54 **Backlash Designation:** Grade e **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 72 transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end Nominallength: 0.218 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.094 inches both ends **Hub Diameter:** 0.344 inches first end **Precision Classification:** Quality number 11 **Special Features:** Mtg holes spaced 90 degrees apart Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 3020-00-765-4911

Spur Gear - Page 2 of 2



Sty				

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300