## NSN 3020-00-765-4914

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-765-4914 **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.5615 inches and 1.5625 inches **Teeth Quantity:** 150 **Backlash Designation:** Grade e **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end Nominallength: 0.240 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.156 inches first end **Face Width:** 0.069 inches **Bore Diameter:** 0.090 inches both ends **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 11 **Special Features:** Mtg holes spaced 90 degrees apart **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Peripheral face, hubless Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A27300

## NSN 3020-00-765-4914

Spur Antibacklash Gear - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.