## NSN 3020-00-765-9224

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-765-9224 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.1042 inches **Teeth Quantity:** 53 Hardness Rating: 34.0 rockwell c and 38.0 rockwell c **Mounting Hole Type And Quantity:** 2 plain axially through flange Nominallength: 0.255 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.135 inches first end **Face Width:** 0.120 inches **Keyway Width:** 0.064 inches both ends **Precision Classification:** Quality number 4 Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Style Designator:** Protruding hub **Test Data Document:** 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:** 

A27300

No Fiig:

**Demilitarization:** 

## NSN 3020-00-765-9224

Spur Gear - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.