NSN 3020-00-768-0129

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-768-0129

Attachment Method:
Mounting hole
Pitch Diameter:
1.5000 inches
Teeth Quantity:
96
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
1.530 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.157 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.813 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/4, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

NSN 3020-00-768-0129

Spur Antibacklash Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):

Mil-a-8625 spec.