NSN 3020-00-772-7909

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-772-7909

Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
2.3750 inches
Teeth Quantity:
76
Bore Style:
W/counterbore both ends
Mounting Hole Type And Quantity:
2 plain axially through hub, first end
Outside Diameter:
2.438 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.800 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Counterbore Depth:
0.625 inches second end
Counterbore Diameter:
0.562 inches second end
Hub Style Designator:
2 steps first end
End Length:
0.062 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.250 inches first end
First Step Length:
0.113 inches first end
First Step Diameter:
0.375 inches first end

Second Step Length: 0.625 inches first end

NSN 3020-00-772-7909

Spur Gear - Page 2 of 2

Fiig: A27300



Second Step Diameter:
0.812 inches first end
Mounting Hole Diameter:
0.109 inches axially through hub, first end
Bolt Hole Circle Diameter:
0.375 inches axially through hub, first end
Material:
Copper alloy 675
Material Specification:
Qq-b-728, class a, comp 1/2 hard /d/ federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No