

View Online at <https://aerobasegroup.com/nsn/3020-00-776-1071>

**Counterbore Diameter:**

1.000 inches

**Counterbore Depth:**

0.031 inches

**Groove Depth:**

0.855 inches

**Groove Width:**

0.532 inches

**Outside Diameter:**

5.062 inches

**Overall Length:**

2.312 inches

**Keyway Width:**

0.252 inches

**Bore Diameter:**

Between 0.875 inches and 0.876 inches

**Bore Length:**

1.312 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.540 inches and 0.546 inches

**V Groove Angle In Deg:**

36.0

**Pitch Diameter:**

3.634 inches

**Material And Location:**

Steel, qq-5-698, comp 1008 through 1020, cond crdq or crdqsky, rim and steel, qq-s-633, comp c1010 through c1020 or c1108 through c1120, hub

**Face Width:**

1.750 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Included

**Counterbore Location:**

Aa end

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**First Step Face Largest Diameter And Location:**

1.625 inches aa end

**First Step Length And Location:**

0.364 inches aa end

**Hub End Outside Diameter And Location:**

1.281 inches aa end and 1.625 inches aa end and 1.281 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.562 inches aa end and 1.000 inches bb end

**Quantity:**

1

**Surface Treatment:**

Enamel

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Enameled

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-a