## NSN 3020-00-777-3131

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-777-3131

Outside Diameter:
22.000 inches
Bore Diameter:
14.750 inches
Bore Length:
0.500 inches
Drilled Hole Diameter:
Between 0.404 inches and 0.411 inches
Pitch Diameter:
19.314 inches
Securing Hole Quantity:
10
Face Width:
0.500 inches
Design Form:
Webbed
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Thru body
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Included
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:

Not included

## NSN 3020-00-777-3131

Sprocket Wheel - Page 2 of 2



T.	1	 Ю:	itc	-	_

6.911 inches

## **Distance From Outside Flange/rim To Hub End And Location:**

0.187 inches aa end and 0.120 inches bb end

Material:

Steel, qq-s-626, fs1345h or steel, qq-s-626, fs4140

Material:

Steel, qq-s-626, fs1345h or steel, qq-s-626, fs4140

Style Designator:

Webbed or spoked

Shelf Life:

N/a

**Unit Of Measure:** 

--

## **Demilitarization:**

Yes - demil/mli

Fiig:

T353-c