NSN 3020-00-779-6337

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-779-6337

| Body Style: |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Webbed, offset, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 10.0940 inches |
| Teeth Quantity: |
| 78 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Type And Quantity: |
| 2 plain axially through body, first end |
| Outside Diameter: |
| 10.341 inches |
| Teeth Type: |
| Single helix |
| Tooth Form: |
| Standard |
| Tooth Direction: |
| Left |
| Proceure Angles |
| Pressure Angle: |
| 20.0000 degrees |
| _ |
| 20.0000 degrees |
| 20.0000 degrees Helix Angle: |
| 20.0000 degrees Helix Angle: 15.0000 degrees |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end Counterbore Diameter: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end Counterbore Diameter: 4.375 inches first end |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end Counterbore Diameter: 4.375 inches first end Hub Style Designator: |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end Counterbore Diameter: 4.375 inches first end Hub Style Designator: Plain both ends |
| 20.0000 degrees Helix Angle: 15.0000 degrees Distance Between Body Face And Recessed Hub End: 0.843 inches second end Face Width: 2.250 inches Bore Diameter: 2.7500 inches both ends Counterbore Depth: 0.250 inches first end Counterbore Diameter: 4.375 inches first end Hub Style Designator: Plain both ends Hub Diameter: |

Bolt Hole Circle Diameter:

3.500 inches axially through body, first end

NSN 3020-00-779-6337

Helical Gear - Page 2 of 2



| Special Features: |
|------------------------------|
| Four mtg holes on second end |

Material:

Steel

Style Designator:

Recessed hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300