## NSN 3020-00-792-4690



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-792-4690 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** Spruance class dd (963), virginia class cgn (41), forrestal class cv Pitch Diameter: 1.3750 inches **Teeth Quantity:** 48 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.138 inches axially through body, first end **Mounting Hole Type And Quantity:** 4 threaded axially through body, first end **Outside Diameter:** 1.562 inches **Tooth Form:** Standard Flange Diameter: 1.250 inches Pilot Length: 0.050 inches **Pressure Angle:** 14.5000 degrees Flange Thickness: 0.250 inches **Face Width:** 0.064 inches **Bore Diameter:** 0.499 inches both ends **Distance From Flat To Radial Center:** 0.6250 inches first end **Hub Diameter:** 0.825 inches between body and flange

**Pilot Diameter:** 1.000 inches Material:

Copper alloy

## NSN 3020-00-792-4690

Spur Gear - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300