NSN 3020-00-794-6046

Internal Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-794-6046

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 4.6880 inches |
| Teeth Quantity: |
| 150 |
| Backlash Designation: |
| Grade a |
| Mounting Hole Type And Quantity: |
| 2 countersunk axially through body, second end |
| Outside Diameter: |
| 5.4600 inches |
| Nominallength: |
| 0.063 inches |
| Teeth Type: |
| Spur |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Body Recess Depth: |
| 0.0330 inches first end |
| Body Recess Diameter: |
| 4.8800 inches first end |
| Face Width: |
| 0.030 inches |
| Precision Classification: |
| Quality number 6 |
| Mounting Hole Diameter: |
| 0.0980 inches axially through body, second end |
| Bolt Hole Circle Diameter: |
| 5.0820 inches axially through body, second end |
| Material: |
| Copper alloy |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Style Designator: |
| Recessed ring |

NSN 3020-00-794-6046

Internal Gear - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300