NSN 3020-00-794-6090

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-794-6090 **Attachment Method:** Mounting hole Pitch Diameter: 1.4062 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.434 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.255 inches first end **Face Width:** 0.120 inches **Bore Diameter:** 0.120 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 303 hub **Material Specification:**

Qq-s-764 federal specification single material response hub **Surface Treatment:** Passivate hub

NSN 3020-00-794-6090

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment Specif	fication:
--------------------------	-----------

Mil-a-8625 military specification single treatment response body

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.