## NSN 3020-00-794-6184



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-794-6184 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2187 inches **Teeth Quantity:** 78 **Bore Style:** W/counterbore both ends **Backlash Designation:** Grade b **Mounting Hole Type And Quantity:** 4 plain axially through hub, first end **Outside Diameter:** 1.250 inches Nominallength: 0.340 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.210 inches first end **Face Width:** 0.130 inches **Bore Diameter:** 0.628 inches both ends **Counterbore Depth:** 0.196 inches both ends **Counterbore Diameter:** 1.075 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 1.165 inches first end **Precision Classification:** Quality number 8 **Mounting Hole Diameter:** 

0.120 inches axially through hub, first end **Bolt Hole Circle Diameter:** 

0.812 inches axially through hub, first end

## **NSN 3020-00-794-6184** Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No