# NSN 3020-00-799-2167

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-799-2167

#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

# **Pitch Diameter:**

Between 0.4886 inches and 0.4896 inches

# **Teeth Quantity:**

47

Bore Style:

Plain both ends

Outside Diameter:

# 0.5084 inches

Tooth Form:

#### Standard

Pressure Angle:

# 20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.281 inches first end

# Face Width:

0.125 inches

# Bore Diameter:

0.125 inches both ends

# Hub Style Designator:

1 step first end

#### End Length:

0.250 inches first end

# **Precision Classification:**

Quality number 10

# End Diameter:

0.186 inches first end

# First Step Length:

0.031 inches first end

# First Step Diameter:

0.250 inches first end

Material:

Aluminum alloy 2024

# Material Specification:

Qq-a-225/6, t4 federal specification single material response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response



# NSN 3020-00-799-2167

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

