NSN 3020-00-800-0192

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-800-0192

Attachment Method:
Mounting hole
Pitch Diameter:
3.1250 inches
Teeth Quantity:
150
Bore Style:
W/ keyway both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 axially through body, first end
Mounting Hole Thread Size:
0.112 inches axially through body, first end
Mounting Hole Type And Quantity:
2 threaded axially through body, first end
Outside Diameter:
3.163 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.347 inches first end
Face Width:
0.188 inches
Bore Diameter:
0.375 inches both ends
Keyway Width:
0.096 inches both ends
Distance From Bore Center To Keyway Bottom:
0.246 inches both ends
Hub Style Designator:
2 steps first end
End Length:
0.031 inches first end
End Diameter:
0.435 inches first end
First Step Length:
0.094 inches first end
First Step Diameter:
0.516 inches first end

NSN 3020-00-800-0192

Spur Antibacklash Gear - Page 2 of 2



Second Step Length: 0.222 inches first end Second Step Diameter: 0.688 inches first end Material: Steel comp 303 first gear Surface Treatment: Passivate Surface Treatment Specification: Mil-std-171, 5.4 military standard single treatment response Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A27300 Mil-std (military Standard): Mil-std-171 spec.