NSN 3020-00-800-5655

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-800-5655

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 2.0000 inches |
| Teeth Quantity: |
| 96 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 32 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.138 inches axially through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Outside Diameter: |
| 2.0407 inches |
| Nominallength: |
| 0.625 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.125 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.234 inches both ends |
| Hub Diameter: |
| 0.438 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Material: |
| Steel comp 416 |
| Material Specification: |
| Qq-s-764, type 416 cond a federal specification single material response |
| Surface Treatment: |
| Passivate |

NSN 3020-00-800-5655

Spur Gear - Page 2 of 2



| Surface Treatment Spec | ific | ation: |
|------------------------|------|--------|
|------------------------|------|--------|

Mil-std-171, finish no. 5.4.1 military standard single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.