NSN 3020-00-800-7933

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-800-7933

| Body Style: |
|---|
| Webbed, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.4375 inches |
| Teeth Quantity: |
| 69 |
| Bore Style: |
| Plain both ends |
| Hardness Rating: |
| 25.0 rockwell c |
| Mounting Hole Type And Quantity: |
| 1 countersunk axially through body, first end and 1 plain axially through body, first end |
| Outside Diameter: |
| 1.4782 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.007 inches first end |
| Face Width: |
| 0.135 inches |
| Bore Diameter: |
| 0.625 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.812 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Mounting Hole Diameter: |
| 0.041 inches axially through body, first end and 0.056 inches axially through body, first end |
| Bolt Hole Circle Diameter: |
| 1.000 inches axially through body, first end |
| Special Features: |
| Mounting holesspaced 36 degrees apart |
| Material: |
| Steel comp 416 |
| Material Specification: |
| Qq-s-763, class 6, type c federal specification single material response |

NSN 3020-00-800-7933

Spur Gear - Page 2 of 2



| Surface Treatment: |
|-------------------------------|
| Passivate |
| Style Designator: |
| Protruding hub, recessed body |
| Shelf Life: |
| |

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300