NSN 3020-00-801-4230

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-801-4230

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| Between 1.1795 inches and 1.1805 inches |
| Teeth Quantity: |
| 85 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Outside Diameter: |
| 1.207 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.218 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.187 inches both ends |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.375 inches first end |
| Precision Classification: |
| Quality number 10 |
| Special Features: |
| Mtg holes 90 degs apart |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize hub |
| Surface Treatment Specification: |
| Mil-s-8625 military specification single treatment response body |
| Style Designator: |
| Protruding hub |
| Furnished Items And Quantity: |
| 1 setscrew |

NSN 3020-00-801-4230

Spur Gear - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: