NSN 3020-00-801-4230

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-801-4230

Body Style:
Plain, solid
Pitch Diameter:
Between 1.1795 inches and 1.1805 inches
Teeth Quantity:
85
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
1.207 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10
Special Features:
Mtg holes 90 degs apart
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize hub
Surface Treatment Specification:
Mil-s-8625 military specification single treatment response body
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew

NSN 3020-00-801-4230

Spur Gear - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: