NSN 3020-00-801-4232

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-801-4232

Body Style:

Plain, solid

Pitch Diameter:

Between 1.0406 inches and 1.0516 inches

Teeth Quantity:

75

Bore Style:

Plain both ends

Backlash Designation:

Grade c

Outside Diameter:

1.068 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.187 inches

Bore Diameter:

0.250 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.500 inches first end

Precision Classification:

Quality number 10

Special Features:

Mtg holes 90 degs apart

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize hub

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response hub

Style Designator:

Protruding hub

Furnished Items And Quantity:

1 setscrew

NSN 3020-00-801-4232

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

