NSN 3020-00-808-4386

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-808-4386

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 0.7744 inches |
| Teeth Quantity: |
| 38 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade b |
| Hardness Rating: |
| 32.0 rockwell c and 36.0 rockwell c |
| Mounting Hole Type And Quantity: |
| 1 plain transversely through hub, first end |
| Outside Diameter: |
| 0.815 inches |
| Nominallength: |
| 0.216 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.116 inches first end |
| Face Width: |
| 0.100 inches |
| Bore Diameter: |
| 0.188 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.375 inches first end |
| Precision Classification: |
| Quality number 8 |
| Mounting Hole Diameter: |
| 0.063 inches transversely through hub, first end |
| Material: |
| Steel comp e4340 |
| Material Specification: |

Mil-s-5000 military specification single material response

NSN 3020-00-808-4386

Spur Gear - Page 2 of 2



| Oxide |
|-------------------|
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |

Mil-std (military Standard):

Surface Treatment:

Mil-s-5000 spec.