# NSN 3020-00-808-4387

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-808-4387

### **Body Style:**

Webbed, offset, with lightening holes

## **Attachment Method:**

Mounting hole

# End Application:

C130 acft

## **Pitch Diameter:**

7.6250 inches

## **Teeth Quantity:**

122

Bore Style:

Plain both ends

#### **Backlash Designation:**

Grade a

#### Hardness Rating:

32.0 rockwell c and 41.0 rockwell c

## Mounting Hole Type And Quantity:

4 plain axially through body, first end

## Outside Diameter:

7.700 inches

### Nominallength:

0.500 inches

## Tooth Form:

Standard

### Pressure Angle:

25.0000 degrees

## Distance Between Body Face And Recessed Hub End:

0.062 inches first end

#### Face Width:

0.500 inches

#### Bore Diameter:

0.906 inches both ends

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

1.595 inches first end

#### Mounting Hole Diameter:

0.198 inches axially through body, first end

## **Bolt Hole Circle Diameter:**

1.250 inches axially through body, first end

# Material:

Steel comp e9310

# NSN 3020-00-808-4387

Spur Gear - Page 2 of 2



## Material Specification:

Ams 6260 assn standard single material response

# Style Designator:

Recessed hub

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A27300