## NSN 3020-00-808-6350

Spur Gear - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/3020-00-808-6350
Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
20.0000 inches
Teeth Quantity:
480
Bore Style:
W/counterbore first end
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Mounting Hole Thread Size:
0.190 inches axially through body, first end
Mounting Hole Type And Quantity:
8 plain axially through body, first end and 2 threaded axially through body, first end
Outside Diameter:
20.083 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Face Width:
0.468 inches
Bore Diameter:
10.313 inches both ends
Counterbore Depth:
0.250 inches first end
Counterbore Diameter:
11.250 inches first end
Mounting Hole Diameter:
0.193 inches axially through body, first end
Bolt Hole Circle Diameter:
10.750 inches axially through body, first end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/4, t4 federal specification single material response

Oxide film

**Surface Treatment:** 

## NSN 3020-00-808-6350

Spur Gear - Page 2 of 2



Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
Hubless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.