NSN 3020-00-810-0302



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-810-0302 **Outside Diameter:** 2.049 inches **Overall Length:** 0.656 inches **Bore Diameter:** 0.4731 inches **Bore Length:** 0.656 inches **Drilled Hole Diameter:** 0.073 inches Pitch Diameter: 1.915 inches **Securing Hole Quantity: Face Width:** 0.110 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 30.0 rockwell c hub and 35.0 rockwell c hub **Counterbore Feature:** Not included **Hole Location:** Located 0.109 in. From face to center of hole through one side only **Keying Facility:** Not included **Securing Method:** Drilled hole **Lightening Hole:**

Included **Protruding Hub Characteristic:** Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

NSN 3020-00-810-0302 Sprocket Wheel - Page 2 of 2



| Teeth Row Quantity: |
|---|
| 1 |
| Teeth Quantity Per Row: |
| 24 |
| Hardness Rating Test Method: |
| Rockwell |
| Teeth Hardness Rating: |
| Between 30.0 rockwell c and 35.0 rockwell c |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.250 inches |
| Hub End Outside Diameter And Location: |
| 0.750 inches both ends and 0.687 inches both ends |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.259 inches both ends and 0.287 inches both ends |
| Material: |
| Steel, mil-s-5626, comp 4140 |
| Material: |
| Steel comp 4140 |
| Material Specification: |
| Mil-s-5626, comp 4140 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Cadmium plated |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-c |
| Mil-std (military Standard): |
| Mil-s-5626 spec. |