## NSN 3020-00-814-8706

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-814-8706 **Body Style:** Plain, solid Pitch Diameter: 0.7500 inches **Teeth Quantity:** 18 **Bore Style:** Plain both ends Hardness Rating: 75.0 rockwell c and 83.0 rockwell c **Outside Diameter:** 0.833 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.187 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 **Special Features:** Mtg holes 90 degs apart Material: Steel comp 303 or steel comp 303se **Material Specification:** Mil-s-7720, comp 303s military specification 1st material response or mil-s-7720, comp 303se military specification 2nd material response **Surface Treatment: Passivate Style Designator:** Protruding hub **Furnished Items And Quantity:** 

N/a

1 setscrew Shelf Life:

## NSN 3020-00-814-8706

Spur Gear - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.