NSN 3020-00-815-2741

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-815-2741

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Clamp |
| Pitch Diameter: |
| Between 0.8323 inches and 0.8333 inches |
| Teeth Quantity: |
| 40 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Outside Diameter: |
| 0.873 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.380 inches first end |
| Face Width: |
| 0.120 inches |
| Bore Diameter: |
| 0.188 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.247 inches first end |
| Clamping Surface Length: |
| 0.380 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Style Designator: |

Protruding hub

NSN 3020-00-815-2741

Spur Gear - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: