## NSN 3020-00-815-7551

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-815-7551

**Body Style:** Plain, solid **Attachment Method:** Clamp Pitch Diameter: Between 1.3115 inches and 1.3125 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.342 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.307 inches first end Face Width: 0.093 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.300 inches first end **Clamping Surface Length:** 0.307 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** 

Mil-a-8625 military specification single treatment response

**Style Designator:** 

Protruding hub

## NSN 3020-00-815-7551

Spur Gear - Page 2 of 2



Shelf I	_ife:
---------	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.