NSN 3020-00-815-7556

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-815-7556

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 0.3115 inches and 0.3125 inches
Teeth Quantity:
20
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.342 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.380 inches first end
Face Width:
0.120 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.247 inches first end
Clamping Surface Length:
0.380 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response

Style Designator: Protruding hub

NSN 3020-00-815-7556

Spur Gear - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: