## NSN 3020-00-815-7559

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-815-7559

Dady Chila		
Body Style: Plain, solid		
Attachment Method:		
Clamp		
Pitch Diameter:		
Between 0.4209 inches and 0.4219 inches		
Teeth Quantity:		
27		
Bore Style:		
Plain both ends		
Backlash Designation:		
Grade c		
Outside Diameter:		
0.452 inches		
Tooth Form:		
Standard		
Pressure Angle:		
20.0000 degrees		
Distance Between Body Face And Protruding Hub End:		
0.380 inches first end		
Face Width:		
0.120 inches		
Bore Diameter:		
0.188 inches both ends		
Hub Style Designator:		
Split first end		
Hub Diameter:		
0.247 inches first end		
Clamping Surface Length:		
0.380 inches first end		
Precision Classification:		
Quality number 10 or quality number 11		
Material:		
Aluminum alloy 2024		
Material Specification:		
Qq-a-225/6, t4 federal specification single material response		
Surface Treatment:		
Anodize		
Surface Treatment Specification:		
Mil-a-8625 military specification single treatment response		
Style Designator:		

Protruding hub

## NSN 3020-00-815-7559

Spur Gear - Page 2 of 2



N/a	
Unit Of	Measure:

Shelf Life:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.