# NSN 3020-00-816-2276

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-816-2276

#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

### **Pitch Diameter:**

Between 2.9995 inches and 3.0000 inches

### **Teeth Quantity:**

192

Bore Style:

Plain both ends

#### Backlash Designation:

Grade b

#### Outside Diameter:

3.030 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.330 inches first end

# Face Width:

0.120 inches

#### Bore Diameter:

0.187 inches both ends

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

0.247 inches first end

#### **Clamping Surface Length:**

0.330 inches first end

#### **Precision Classification:**

Quality number 13 or quality number 14

#### Material:

Aluminum alloy 2024

#### **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

# Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

# Style Designator:

Protruding hub



# NSN 3020-00-816-2276

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.

