## NSN 3020-00-816-4676

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-816-4676

Webbed, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 1.0097 inches and 1.0104 inches
Teeth Quantity:
97
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
1.030 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.205 inches first end
Face Width:
0.120 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.183 inches first end
Clamping Surface Length:
0.263 inches first end
Precision Classification:
Quality number 12
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hub, recessed body

## NSN 3020-00-816-4676

Spur Gear - Page 2 of 2



Sneit	Lite:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.