

View Online at <https://aerobasegroup.com/nsn/3020-00-816-4678>

**Body Style:**

Webbed, offset, solid

**Attachment Method:**

Clamp

**Pitch Diameter:**

Between 1.1243 inches and 1.1250 inches

**Teeth Quantity:**

72

**Bore Style:**

Plain both ends

**Backlash Designation:**

Grade d

**Outside Diameter:**

1.155 inches

**Tooth Form:**

Standard

**Pressure Angle:**

20.0000 degrees

**Distance Between Body Face And Protruding Hub End:**

0.045 inches second end

**Face Width:**

0.120 inches

**Bore Diameter:**

0.250 inches both ends

**Hub Style Designator:**

Split first end

**Hub Diameter:**

1.005 inches second end

**Clamping Surface Length:**

0.220 inches first end

**Precision Classification:**

Quality number 12

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-225/6, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Protruding hubs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A27300

**Mil-std (military Standard):**

Mil-a-8625 spec.