## NSN 3020-00-816-4678

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-816-4678

Body Style:
Webbed, offset, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 1.1243 inches and 1.1250 inches
Teeth Quantity:
72
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
1.155 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.045 inches second end
Face Width:
0.120 inches
Bore Diameter:
0.250 inches both ends
<b>Hub Style Designator:</b>
Split first end
Hub Diameter:
1.005 inches second end
Clamping Surface Length:
0.220 inches first end
Precision Classification:
Quality number 12
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hubs

## NSN 3020-00-816-4678

Spur Gear - Page 2 of 2



N/a		
Unit	Of	Mea

Shelf Life:

sure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.