## NSN 3020-00-816-4706

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-816-4706

Body Style:
Plain, with lightening holes
Attachment Method:
Clamp
Pitch Diameter:
Between 3.7490 inches and 3.7500 inches
Teeth Quantity:
240
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
3.780 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.094 inches
Bore Diameter:
0.120 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.158 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.172 inches first end
First Step Length:
0.060 inches first end
First Step Diameter:
0.250 inches first end
Material:
Steel comp 420
Material Specification:
Qq-s-763, class 420, cond a federal specification single material response
Surface Treatment:
Parameter

Passivate

## NSN 3020-00-816-4706

Spur Gear - Page 2 of 2

**Fiig:** A27300

Mil-std (military Standard):

Mil-s-5002 spec.



Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No