NSN 3020-00-816-4706

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-816-4706

Body Style:

Plain, with lightening holes

Attachment Method:

Clamp

Pitch Diameter:

Between 3.7490 inches and 3.7500 inches

Teeth Quantity:

240

Bore Style:

Plain both ends

Backlash Designation:

Grade c

Outside Diameter:

3.780 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.218 inches first end

Face Width:

0.094 inches

Bore Diameter:

0.120 inches both ends

Hub Style Designator:

1 step first end

End Length:

0.158 inches first end

Precision Classification:

Quality number 10 or quality number 11

End Diameter:

0.172 inches first end

First Step Length:

0.060 inches first end

First Step Diameter:

0.250 inches first end

Material:

Steel comp 420

Material Specification:

Qq-s-763, class 420, cond a federal specification single material response

Surface Treatment:

Passivate

NSN 3020-00-816-4706

Spur Gear - Page 2 of 2



Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5002 spec.