NSN 3020-00-816-8211

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-816-8211

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 1.1240 inches and 1.1250 inches
Teeth Quantity:
72
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
1.155 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.015 inches second end
Face Width:
0.120 inches
0.120 inches Bore Diameter:
Bore Diameter:
Bore Diameter: 0.125 inches both ends
Bore Diameter: 0.125 inches both ends Hub Style Designator:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11 Material:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11 Material: Aluminum alloy 2024
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11 Material: Aluminum alloy 2024 Material Specification:
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11 Material: Aluminum alloy 2024 Material Specification: Qq-a-225/6, t4 federal specification single material response
Bore Diameter: 0.125 inches both ends Hub Style Designator: Split first end Hub Diameter: 0.183 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 10 or quality number 11 Material: Aluminum alloy 2024 Material Specification: Qq-a-225/6, t4 federal specification single material response Surface Treatment:

Style Designator: Protruding hubs

NSN 3020-00-816-8211

Spur Gear - Page 2 of 2



Sneir	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.