NSN 3020-00-816-8309

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-816-8309

| Body Style: |
|--|
| Webbed, solid |
| Pitch Diameter: |
| 1.6250 inches |
| Teeth Quantity: |
| 26 |
| Bore Style: |
| Plain both ends |
| Hardness Rating: |
| 35.0 rockwell c and 45.0 rockwell c |
| Outside Diameter: |
| 1.700 inches |
| Nominallength: |
| 1.100 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.370 inches both ends |
| Face Width: |
| 0.360 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Outside Radius: |
| 0.310 inches |
| End Diameter: |
| 0.393 inches both ends |
| First Step Length: |
| 0.060 inches second end |
| First Step Diameter: |
| 0.500 inches second end |
| Material: |
| Steel comp e4340 |
| Material Specification: |
| Mil-s-5000 military specification single material response |
| Surface Treatment: |
| Oxide |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |

NSN 3020-00-816-8309

Spur Gear - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.