# NSN 3020-00-818-2370

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-818-2370

#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

## **Pitch Diameter:**

Between 0.7802 inches and 0.7812 inches

## **Teeth Quantity:**

75

Bore Style:

Plain both ends

#### Backlash Designation:

Grade c

#### Outside Diameter:

0.801 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.054 inches second end

# Face Width:

0.120 inches

#### Bore Diameter:

0.125 inches both ends

#### Hub Style Designator:

Split first end

### Hub Diameter:

0.183 inches first end

#### Clamping Surface Length:

0.241 inches first end

#### **Precision Classification:**

Quality number 10 or quality number 11

#### Material:

Aluminum alloy 2024

#### **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

# Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

#### Style Designator:

Protruding hubs



# NSN 3020-00-818-2370

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.

