NSN 3020-00-818-5733



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-818-5733 **Body Style:** Webbed, offset, solid Pitch Diameter: 1.5312 inches **Teeth Quantity:** 49 **Bore Style:** 10a w/ keyway both ends **Backlash Designation:** Grade b Hardness Rating: 40.0 rockwell c and 44.0 rockwell c **Outside Diameter:** 1.594 inches **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.153 inches first end **Face Width:** 0.227 inches **Bore Diameter:** 0.250 inches both ends **Keyway Width:** 0.064 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.158 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.440 inches first end **Precision Classification:** Quality number 8 Material: Steel comp e4340

Mil-s-5000 military specification single material response **Style Designator:**One protruding hub, one flush hub

Shelf Life:

N/a

Material Specification:

NSN 3020-00-818-5733

Spur Gear - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.