# NSN 3020-00-821-1344

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-821-1344

# Groove Depth:

0.563 inches and 0.563 inches and 0.625 inches

# Groove Width:

 $0.500 \ \text{inches}$  and  $0.500 \ \text{inches}$  and  $0.656 \ \text{inches}$ 

# **Overall Length:**

3.125 inches

# Keyway Width:

0.125 inches

Thread Size:

7/16-14

# Bore Diameter:

1.000 inches

# Bore Length:

1.938 inches

# Distance From Center Of Bore To Bottom Of Keyway:

0.563 inches

# V Groove Angle In Deg:

20.0

#### Securing Hole Quantity:

2

#### Face Type:

Step groove

#### Material And Location:

Steel

#### Face Width:

2.375 inches

#### **Design Form:**

Webbed

#### Bore Type:

Straight

#### Groove Quantity:

3

# Counterbore Feature:

Not included

# Step Outside Diameter:

9.000 inches

# Hole Location:

Thru pulley 180 degrees apart

# Keying Facility:

Included

# Keying Facility Type:

Keyway

# **NSN 3020-00-821-1344** Cone Pulley - Page 2 of 2

Securing Method:	
Threaded hole	
Split Hub Feature:	
Not included	
Web/spoke Relationship To Face Centerline:	
Offset	
Lightening Hole:	
Not included	
Integral Cooling Vane:	
Not included	
Groove Shape:	
V	
Standard V-belt Section Designation For Which Designed:	
A and a and b	
Protruding Hub Characteristic:	
Plain	
Bore Bearing:	
Not included	
Hub End Outside Diameter And Location:	
1.750 inches aa end	
Distance From Outside Flange/rim To Hub End And Location:	
0.813 inches aa end and 1.125 inches bb end	
V Groove Pitch Diameter:	
8.500 inches	
Quantity:	
1	
Style Designator:	
Webbed or spoked	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Νο	
Fiig:	
Т353-b	

