## NSN 3020-00-821-1344

0.563 inches and 0.563 inches and 0.625 inches

0.500 inches and 0.500 inches and 0.656 inches

**Distance From Center Of Bore To Bottom Of Keyway:** 

Cone Pulley - Page 1 of 2

**Groove Depth:** 

**Groove Width:** 

Overall Length: 3.125 inches Keyway Width: 0.125 inches Thread Size:

7/16-14

Bore Diameter: 1.000 inches Bore Length: 1.938 inches

0.563 inches



View Online at https://aerobasegroup.com/nsn/3020-00-821-1344

V Groove Angle In Deg:
20.0
Securing Hole Quantity:
2
Face Type:
Step groove
Material And Location:
Steel
Face Width:
2.375 inches
Design Form:
Webbed
Bore Type:
Straight
Groove Quantity:
3
Counterbore Feature:
Not included
Step Outside Diameter:
9.000 inches
Hole Location:
Thru pulley 180 degrees apart
Keying Facility:
Included
Keying Facility Type:
Keyway

## **NSN 3020-00-821-1344**Cone Pulley - Page 2 of 2



Securing Method:
Threaded hole
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Offset
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Standard V-belt Section Designation For Which Designed:
A and a and b
Protruding Hub Characteristic:
Plain
Bore Bearing:
Not included
Hub End Outside Diameter And Location:
1.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.813 inches aa end and 1.125 inches bb end
V Groove Pitch Diameter:
8.500 inches
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-b