NSN 3020-00-822-1913

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-822-1913 **Attachment Method:** Clamp Pitch Diameter: 0.7500 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Outside Diameter:** 0.765 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.051 inches second end **Face Width:** 0.094 inches **Bore Diameter:** 0.120 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.205 inches second end **Clamping Surface Length:** 0.185 inches first end **Precision Classification:** Quality number 13 Material: Aluminum alloy 6061 **Material Specification:** Qq-a-225/8, t6 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Protruding hubs Shelf Life: N/a

Unit Of Measure:

NSN 3020-00-822-1913

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.