NSN 3020-00-822-3221

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-822-3221

Attachment Method:
Mounting hole
Teeth Quantity:
76
Bore Style:
Plain both ends
Backlash Designation:
Grade b
Hardness Rating:
85.5 rockwell superficial 15-n teeth
Mounting Hole Type And Quantity:
2 countersunk axially through body, first end
Nominallength:
0.760 inches
Tooth Form:
Special
Pressure Angle:
20.0000 degrees
Face Width:
0.335 inches
Bore Diameter:
0.690 inches both ends
Outside Radius:
1.343 inches
Mounting Hole Diameter:
0.190 inches axially through body, first end
Bolt Hole Circle Diameter:
1.162 inches axially through body, first end
Special Features:
Two, seven tooth sectors located 90 degrees apart, tooth face in line w/ bore
Material:
Steel comp 4340
Material Specification:
Mil-s-5000 military specification single material response
Surface Treatment:
Cadmium body
Surface Treatment Specification:
Qq-p-416, type 1, class 2 federal specification single treatment response body
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3020-00-822-3221

Spur Gear Sector - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.