NSN 3020-00-823-5596

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-823-5596

Plain, solid							
Attachment Method:							
Mounting hole							
Serration Quantity:							
22 first end							
Pitch Diameter:							
4.0000 inches							
Teeth Quantity:							
16							
Bore Style:							
Serrated first end							
Serration Pitch Diameter:							
0.4583 inches first end							
Hardness Rating:							
30.0 rockwell c and 35.0 rockwell c							
Mounting Hole Type And Quantity:							
1 plain axially through body, second end							
Outside Diameter:							
4.640 inches							
Pressure Angle:							
25.0000 degrees							
Distance Between Body Face And Protruding Hub End:							
1.687 inches first end							
Body Recess Depth:							
1.047 inches first end							
Face Width:							
0.250 inches							
Bore Diameter:							
1.688 inches first counterbore, second end							
Bore Depth:							
0.937 inches second counterbore, second end							
Hub Style Designator:							
Plain first end							
Hub Diameter:							
3.000 inches first end							
Mounting Hole Diameter:							
0.437 inches axially through body, second end							
Material:							
Material: Steel comp 4140							

NSN 3020-00-823-5596

Spur Gear - Page 2 of 2



S	ur	fa	се	T	re	at	m	eı	າt:

Phosphate manganese

Surface Treatment Specification:

Mil-p-16232, type m, class 1 military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-13048 spec.